

THE COST-EFFICIENT POWERHOUSE

Boss Standard

When it comes to high performance and cost-effective pressure isolation, Boss Standard frac plugs have no equal. Compared to conventional frac plugs, Boss Standard plugs are easy to deploy, hold high pressure, and drill out in eight to 15 minutes. Made from the highest-grade composite materials—without any tungsten carbide—this bullet-proof design yields a predictable drillout every time.

This plug is ideal for high bottom pressures or high reverse flow rates.

FEATURES

- + No tungsten carbide
- + Extreme resistance to presets
- + Fast drillout
- + Minimal casing damage
- + 10 KSI+ differential at 250°F
- + Rated up to 10K PSI

AVAILABILITY

- + Ball Drop
- + Ball-in-Place
- + Ball Check
- + Bridge

CASING SIZES

- + 4.375" OD: 5.50" 17#, 20#, and 23#
- + 4.250" OD: 5.50" 20#, 23#, and 26#
- + 4.125" OD: 5.50" 26#
- + 3.875" OD: 5.00" 18#
- + 3.650" OD: 4.50" 11.6# and 13.5#
- + 3.500" OD: 4.50" 13.5#, 15.1#, and 16.6#
- + 3.063" OD: 3.19" through 3.55", ID patch and liner



Contact WellBoss Today

theWellBoss.com | 281.820.2545